



Application

- FORTAX® 6600 assembling adhesive is used for permanent and secure sealing of facades and for secure bonding of junction and sealing films



Application Notes

- FORTAX® 6600 assembling adhesive is compatible with paint coating
- Due to the variety of available varnishes on the market, we recommend performing preliminary tests
- If used together with alkyd resin colours, the drying process may be slowed down
- After cleaning with acetone the surface may be coated once again

Technical Data

Raw material base	MS hybrid polymer
Consistency	paste-like
Density (DIN 53479)*	1.5 g/cm ³
Shore A Hardness (DIN 53505)*	55 +/- 3
Full hardening	approx. 3 mm after 24 h
Elongation at break	500 %
Temperature stability	-40 °C to +80 °C
Application temperature	at +5 °C to +40 °C
Storage	+5 °C to +25 °C, frost free
Shelf life	12 months in unopened cartridge / sausage

*according to the respective DIN

Further technical data about FORTAX® 6600 available upon request.
Subject to change without notice in line with product advancements.

Gerband® adhesive tapes are used by a very diverse customer base for a wide range of technical and industrial applications. The demands made on Gerband® products vary considerably from application to application. We strongly advise users to test the product's suitability for their own particular requirement. All data and recommendations contained in this Technical Data Sheet are based on our own test results and practical experience and are aimed at helping customers select the appropriate tape for a given application. This information is provided without liability. We reserve the right to change the technical specification without prior notice. Samples are available free of charge. Our sales team is also available to assist customers with their tape.

Product Description

Elastic one-component adhesive and sealing compound on the basis of MS hybrid polymers.

- Quick moisture curing
- Very good resistance to weathering
- Neutral cross-linking
- Odourless

Packaging Unit

- 12 cartridges á 290 ml / carton
- 12 sausages á 600 ml / carton

as of April 2010 · replaces edition of November 2009

Certified according to
DIN ISO 9001 and 14001
Reg.-Nr. 56398-QM



Gerlinger GmbH & Co. KG
Adhesive Tape Factories
Jaumann-Industriepark 5
D-86720 Nördlingen, Germany
Telephone +49 (0) 90 81 213-0
Telefax +49 (0) 90 81 213-100
e-Mail info@gerband.de
Internet www.gerband.de